

Project Name: _____

Fixture Type: _____

Date: _____



2" ELIUM™ Commercial Downlights

IC rated up to 1,500 lumens and Non-IC options up to 3,500 lumens. 120–277V, Triac, ELV, 0–10V.

New Construction and Remodel/Retrofit. Round and Square, Flanged.

2" ELIUM TRIMS



Round Bevel




Round Pinhole



Round Wall Wash



Square Bevel



Square Pinhole



Square Wall Wash

FEATURES

- 3 Part System: Frame, Module, & Trim
- UL Listed for direct contact with insulation up to 1,500 lumens, non-IC up to 3,500 lumens
- Title 24 JA8–2025–E Compliant up to 1,500 lumens
- Lockable gear adjustment up to 35° center axis tilt and 359° rotation, adjusted by hand and locked with 3/32" Allen Key from below the ceiling
- Patented LED Module with in field changeable optic
- Standard Dimming to 1% with 0–10V, Triac and ELV dimmers. Optional 0.1% dimming
- Compatible with ceilings up to 2" thick (2" thick ceilings may limit tilt)
- Flanged options only
- Precision single piece die-cast trims
- 50,000 hours lifespan L70


SPECIFICATIONS

WATTAGE:	6W – 32W
LUMENS:	750 lm – 3500 lm
VOLTAGE:	120–277V
COLOR TEMP:	2700K, 3000K, 3500K, 4000K,
DIMMABLE:	0–10V, Triac, ELV (1%), 0–10V (0.1%), DALI-2 (0.1%), LUTRON ATHENA (0.1%)
BEAM ANGLE:	15°, 24°, 36°, 50°
CRI:	95+

2" ELIUM™ 3-PART SYSTEM: FRAME, MODULE & TRIM



LOCKABLE HOT AIMING GEAR ADJUSTMENT FROM BELOW



1. Specify frame part number			FRAME				Example: LUCM29RDX07	
ELIUM	SIZE	STYLE	DRIVER		LUMENS/WATTAGE	OPTIONAL EM		
LUCM								
LUCM	29 2"	RD Round (New Construction)	X	120-277V, 0-10V, Triac/ELV (1%)	07 ³ 750 lm (6W)	(Blank) No EM		
		SQ Square (New Construction)	ED ²	eldoLed, 0-10V (0.1%)	10 ³ 1000 lm (8W)	E1 8W EM, 90 min		
	REM ¹	Remodel/Retrofit	AL ²	eldoLed, DALI-2 (0.1%)	12 ³ 1250 lm (11W)	E2 15W EM, 90 min		
			LN ²	Lutron Athena Node (0.1%)	15 ³ 1500 lm (14W)	E5 25W EM, 90 min		
					20 ⁴ 2000 lm (19W)			
					25 ⁴ 2500 lm (23W)			
					30 ⁴ 3000 lm (29W)			
					35 ⁴ 3500 lm (32W)			

¹ Remodel is available up to 2500 lm, no frame. ² Special order, extended lead time of 2-10 weeks may apply. ³ IC rated for direct contact with insulation, cUL up to 1500 lumens (14W). ⁴ Non-IC, for use without insulation, or keep insulation 3" away from fixture. 2000 (19W) – 3500 (32W) lumens.

2. Specify module part number		MODULE		Example: LUCM3530D-S	
ELIUM	TYPE	COLOR TEMPERATURE		BEAM	
LUCM					
LUCM	35 CREE PRO9 Chip, CRI 95+	27D	2700K	-S	15°
		30D	3000K	-N	24°
		35D	3500K	-F	36°
		40D	4000K	-W	50°
				-XX	36° installed, with 15°, 24° & 50° lenses included

SECONDARY MODULE OPTICS*			
L45	L57	L51	L49
Black Louver	White Louver	CCT Reducer	Frosted Lens

*Module Fits up to 4 secondary optics.
*Not for use with 29W & 30W.

3. Specify trim part number			TRIM				Example: LU29RD10T72W	
ELIUM	SIZE	SHAPE	STYLE	TRIM	LENS	FINISH		
LU								
LU	29 2"	RD Round	10 Bevel	T Flanged ²	(Blank)	Open, No Lens ^{3,5}	W All White ⁷	
		SQ Square	27 Pinhole		72	Clear Lens ^{4,5}	BB All Black	
			33 Wall Wash ¹		83	Difused Lens ^{4,5}	BZ All Bronze	
					94	Linear Lens ^{4,6}	CC Custom Color	
							HH All Haze	
							HW Haze with White Flange ⁸	


¹ Requires Linear Lens (94 lens option)
² For ceiling thickness up to 2"
³ Damp Location
⁴ Wet Location
⁵ Not available for Wall Wash Trim

⁶ For Wall Wash trim only
⁷ White trims are field paintable
⁸ For Flanged Bevel and Wall Wash only



ACCESSORIES	
ALLEN KEY: LU332ALLEN	

PRODUCTS



Housings



2" ROUND





2" SQUARE
45° bidirectional collar rotation
for square alignment



Remodel/Retrofit




ELIUM Remodel/Retrofit




Module



ELIUM Commercial Module



Accessories



Black Louver
L45



White Louver
L57



CCT Reducer
L51



Frosted Lens
L49





Lenses
LUP15D (15°)
LUP24D (24°)
LUP36D (36°)
LUP50D (50°)


Trims




Round Bevel





Round Pinhole




Round Wall Wash



Square Bevel



Square Pinhole



Trims



Square Wall Wash




White



Bronze




Haze/White
Flange



Black



All Haze



TECHNICAL SPECIFICATIONS

The ELIUM Commercial Downlight is a modular, high-performance recessed lighting system designed for versatility and ease of installation. The system consists of three key components: Frame, Module, and Trim Mechanism. The module securely twists onto the trim mechanism and connects to the housing via a quick-connect system. Both the module and driver are fully serviceable from below the ceiling.

HOUSING:

- Shallow height requires less than 5" of ceiling space.
- High-strength hanger bars can be easily nailed to wood joists or slid onto T-Grid drop ceilings. Adjustable from 7.5" to 24" Wide.
- Universal housing works with flanged, flangeless & millwork applications.
- Accessible driver mounted on the frame for easy servicing.
- Rotatable square collar ensures precise square alignment.
- Knockouts for easy wiring: Seven 1/2" trade-size conduit knockouts and 4 EZ-Romex cable traps

EMERGENCY OPTIONS:

- 90-minute emergency battery backup with remote test switch.
- 25W emergency backup accessible from below.

OPTICS:

- Precision-engineered PIR optics available in 15°, 24°, 36° and 50° beam spreads.
- Field-changeable secondary lenses available. No accessory holder required. Module can hold up to 4 secondary lenses.

LED TECHNOLOGY:

- 95+ CRI for exceptionally accurate color rendering.
- 50,000-hour L70 lifespan based on LM80 test standards.
- Advanced thermal management with integrated heat sink.
- Instant-on to full brightness with no visible LED pixilation.

ADJUSTABILITY:

- Adjustable from below the ceiling while keeping the light centered with the trim opening.
- 35° tilt by hand adjustment, set using a 3/32" Allen key with an automatic locking mechanism ensures secure positioning.
- 359° rotation for precise aiming.

TRIM:

- Diecast aluminum powder coated trim.
- White finish is field paintable.

MODULE - LUMEN MULTIPLIER

CCT	MULTIPLIER	BEAM ANGLE	MULTIPLIER	LENSES	MULTIPLIER
2700K	0.96	15°	0.84	L45 - Black Louver	0.95
3000K	1	24°	0.89	L57 - White Louver	0.96
3500K	1.05	36°	1	L47 - Optic Spread	0.93
4000K	1.085	50°	1.065	L49 - Frosted Lens	0.85
				L51 - CCT Reducer	0.90
				Trim 72 - Clear Lens	0.95
				Trim 83 - Solite Lens	0.87

DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELIUM Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
120V - Triac/ELV Dimmers for LU29RD, LU29SQ, LU37RD, LU37SQ, LU45RD & LU45SQ Series			
Leviton	120V AC 60Hz, 300W Electronic Low Voltage, 400 Volt Amp, Single Pole, 3-Way	IPE04	1% - 100%
	120V AC 60Hz, 300W CFL or 600W Incandescent, 400 Volt Amp, Single Pole, 3-Way	6673-10W	1% - 100%
	120V AC, 600W Incandescent with LED Locator, Single Pole, 3-Way	VP106	1% - 100%
	120V AC 60Hz, 500W Incandescent with LED Level Indicator, Single Pole, 3-Way	6161	1% - 100%
	120V AC, 150W LED/CFL or 600W Incandescent, Single Pole, 3-Way	6674	1% - 100%
Lutron	120V AC, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	RRD-6CL	1% - 100%
	120V AC 60Hz, 150W LED/CFL/Incandescent/Halogen, Single Pole, 3-Way	DVCL-153P	1% - 100%
	120V 60Hz, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	TGCL-153P	1% - 100%
	120V AC 60Hz, 300W Electronic Low Voltage, 3-Way, Commercial/Residential Application	DVELV-303P	1% - 100%
	120V, 600W Incandescent/Halogen, Single Pole, Residential Indoor Application	TG-600P	1% - 100%
	120V, 1000W Incandescent or 600W Magnetic Low Voltage, Single Pole, 3-Way	CT103P	1% - 100%
	120V AC 60Hz, 600W Electronic Low Voltage, Single Pole/Multi-Location	MAELV600	1% - 100%
	120V AC 60Hz, 500W Electronic Low Voltage, Single Pole/Multi-Location	FAELV500	1% - 100%
	120V AC 60Hz, 600W Incandescent/Halogen, Single Pole, Slide-to-Off Dimmer	S-600P	1% - 100%
	120V AC 60Hz, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	SCL-153P	1% - 100%
	Caséta® Wireless Dimmer	PD-6WCL	1% - 100%
	120V AC 60Hz, Low Voltage Load Type, 150W Single Pole	DVLV-600P	5% - 100%
	120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Residential and Commercial Application	DV-603P	1% - 100%
	120V AC, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	MA-PRO	1% - 100%
	120V AC 60Hz, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	MACL-153M	1% - 100%

***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELIUM Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
120V - Triac/ELV Dimmers for LU29RD, LU29SQ, LU37RD, LU37SQ, LU45RD & LU45SQ Series			
Eaton	120V AC, 300W LED/CFL or 600W Incandescent/MLV/Halogen, Single Pole, 3-Way	TAL06P1-C1	1% - 100%
Cooper	120V AC 60Hz, 300W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	SLC03P / DAL06P	1% - 100%
	120V AC 60Hz, 300W LED/CFL or 600W Incandescent, Single Pole, 3-Way, Residential	DLC03P	1% - 100%
	120V AC 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way	RI061-VW-K2	1% - 100%
	120V AC 60Hz, 300W LED/CFL/ Incandescent/Halogen, Single Pole, 3-Way	AAL06A-C2	1% - 100%
Lightolier	120V, 260W Incandescent/Halogen, Single Pole, 3-Way	ZP260QEW	1% - 100%
0-10V Type Dimmers - 120/277V for LU29RD, LU29SQ, LU37RD, LU37SQ, LU45RD & LU45SQ Series			
Lutron	120/277V AC, 0-10V LED/CFL Ballast, Single Pole, 3-Way	NFTV	1% - 100%
	120/277V AC, 0-10V, Single Pole, 3-Way, Commercial and Residential, Indoor Application	DVSTV	1% - 100%
	120/277V AC 50/60Hz, 0-10V LED/CFL Ballast, Single Pole, 3-Way, Indoor Application	DVTV	1% - 100%
Leviton	120/277V AC 60Hz, 0-10V LED/CFL Ballast, Single Pole, 3-Way	IP710-DL	1% - 100%

***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.

